



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 622 760 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
15.12.1999 Bulletin 1999/50

(51) Int Cl.⁶: **G06K 19/077**, G11C 5/00,
H01L 21/56, H01L 23/31

(21) Application number: **94301681.6**

(22) Date of filing: **09.03.1994**

(54) **External storage device and external storage device unit**

Externe Speicheranordnung und externe Speicheranordnungseinheit

Dispositif d'une mémoire externe et unité de mémoire externe

(84) Designated Contracting States:
DE FR GB

(30) Priority: **28.04.1993 JP 10288493**

(43) Date of publication of application:
02.11.1994 Bulletin 1994/44

(73) Proprietor: **KABUSHIKI KAISHA TOSHIBA**
Kawasaki-shi, Kanagawa-ken 210-8572 (JP)

(72) Inventor: **Iwasaki, Hiroshi**
c/o Intellectual Property Division
Tokyo (JP)

(74) Representative: **Freed, Arthur Woolf et al**
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

(56) References cited:
EP-A- 0 338 080 **FR-A- 2 359 464**

- **PATENT ABSTRACTS OF JAPAN** vol. 014, no. 166 (E-0911)30 March 1990 & JP-A-02 022 849 (NEC CORP) 25 January 1990
- **PATENT ABSTRACTS OF JAPAN** vol. 017, no. 599 (E-1455)2 November 1993 & JP-A-05 183 094 (NECIC MICROCOMPUT SYST LTD) 23 July 1993

Note. Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The invention relates to external storage devices capable of recording and saving various data, a method of producing the external storage devices, and external storage device unit. More specifically, the invention relates to an external storage device exchangeably used for storage equipment and devices as an external storage medium, and a method of readily producing the external storage device, and an effective utilization of the external storage device.

[0002] Storage devices or memory elements, which are capable of recording and saving various data, have been utilized in two systems, namely, one is incorporated and fixed within storage equipment or devices, and the other is releasably or exchangeably incorporated in the storage equipment or devices. For the external storage devices which can optionally be attached or detached or freely removed in the storage equipment or devices, for example, floppy disk devices can be attached and detached by one touch operation. Therefore, the floppy disks being the recording mediums can separately be used depending on purpose and object to record and save the data, whereby easier data reduction can advantageously be obtained.

[0003] However, a problem arises in the floppy disks described, where the data occasionally disappears on recording or saving the data to produce less reliability in addition to slower access time. When producing the smaller sized floppy disks in response to a miniaturization policy, a storing area of the storage medium is correspondingly smaller to reduce storage capacity, thus thus limits practical use thereof.

[0004] On the other hand, semiconductor memory devices used as an external storage device such as IC memory cards can largely solve the drawbacks in the floppy disks, where the IC memory cards generally exhibit graded reliability of recording and saving the data and relatively rapid access time.

[0005] The IC memory cards comprise, a functional circuit in which circuit components containing the semiconductor memory devices or elements are mounted on substrates, a resin casing attached therein with the functional circuit as an inside attachment, a cover for coating and sealing both opening surfaces of the resin casing, and external connection terminals such as two piece connectors which are attached on one edge of the resin casing and electrically connect the functional circuit and the storage equipment / device. However, the IC memory cards are assembled with a large amount of components and parts, where a relatively complicated structure is required with limitation to a thickness of the IC memory card. Further, disadvantages arise because of lower cost performance or production yields on mass production in addition to the less releasability for the storage equipment/devices or fluctuated releasability on function.

[0006] JP-A-02022849 and JP-A-05183094 both dis-

close a semiconductor device having insertion openings for inserting plug-in electrodes. All of the plug-in electrodes are inserted in the same direction, so that one can remove the device from the substrate simply by pulling. JP-A-02022849 discloses a semiconductor device with the features of the preamble of claim 1.

[0007] An object of the invention is to provide an external storage device formed by simplified process.

[0008] Another object of the invention is to provide an external storage device having a high releasability with a high reliable function as an external storage medium.

[0009] Further another object of the invention is to provide a method of producing a high reliable external storage device with graded production yields.

[0010] Still another object of the invention is to provide an external storage device unit formed by simplified process.

[0011] Still further another object of the invention is to provide an external storage device unit having a high releasability with a reliable superior function as an external storage medium.

[0012] An external storage device according to a first aspect of the present invention is defined in claim 1.

[0013] An external storage device according to a second aspect of the present invention is defined in claim 8. Preferred features are specified in the dependent claims.

Fig. 1 is a perspective view showing essentials of an example of an external storage device according to the invention;

Fig. 2 is a perspective line plan view showing essentials of an example of an external storage device according to the invention;

Fig. 3 is a schematic sectional view showing essentials of a preferred embodiment in producing an external storage device according to the invention;

Fig. 4 is a schematic sectional view showing essentials of another preferred embodiment in producing an external storage device according to the invention;

Fig. 5 is a perspective view showing a broken down example of an outline of an external storage device unit according to the invention;

Fig. 6 is a perspective view showing a broken down example of essentials of an external storage device unit according to the invention;

Fig. 7 is a perspective view showing a broken down example of essentials of another external storage device unit according to the invention;

Fig. 8 is a perspective view showing an example of a different structure of an external storage device unit according to the invention; and

Fig. 9 is a perspective view showing an example of a further another structure of an external storage device unit according to the invention.

Embodiment 1

[0014] Fig. 1 is a perspective illustration of outline of an example of an external storage device according to the invention, and Fig. 2 is a perspective line plan view of an outline of an example of an external storage device according to the invention. In this embodiment, an external storage device 1 is configured in that a NAND type flash memory device 2 is made up on a frame substrate by a wire bonding method to produce a main body thereof sized of length 40 mm and width about 30 mm. The external storage device main is formed into a thin plate shape coated and mold sealed by generally used semiconductor element molding resin such as epoxy based resin or the like. A NAND type flash memory device 2 may be bonded by the TAB (Tape Automated Bonding) system as another system. In this embodiment, on input / output portions of the NAND type flash memory device 2, recessed external connection terminals 5 for electrically connecting by a wire bonding 4 is led and exposed, in a manner of slightly forming recessed surfaces 5a, on end surfaces of opposing edges in a thin plate shape formed by coated and sealed.

[0015] In a method of producing the external storage device, Figs. 3 and 4 are sectional views schematically showing a preferred embodiment of a method of producing the external storage device. First, the control proceeds to preparation for the NAND type flash memory device 2 provided with the required external connection terminals 5. An example of such NAND type flash memory device 2 to be prepared is of a NAND type and is assembled in that the recessed shaped external connection terminals 5 is electrically connected and led outside by the wire bonding system. The NAND type flash memory device 2 is attached on a metallic frame (not shown) and may preferably be fixed tentatively with a lead 5b which is led outside. On the other hand, the control proceeds to preparation for a disassemble type mold provided on its predetermined inside-walls with a protruded terminal shaped protrusion 6a mated with a recessed surface 5a of each recessed shaped external connection terminal 5 which is led outside, with respect to the NAND type flash memory device 2. The mold 6 is formed into the disassemble type which includes a side wall 6b formed by combining squared side-walls, a bottom wall 6c engaging and sealing squared top and bottom openings formed from the side walls 6b, and a top wall 6d. A pair of side walls 6b opposing each other from among the side walls 6b are arranged with a group of terminal shaped protrusions 6a opposing each other and corresponding to the recessed surfaces 5a of the external connection terminals 5 of the NAND type flash memory device 2.

[0016] The disassemble type mold 6 registers, engages, and arranges the external connection terminals 5 of the NAND type flash memory device 2 with the corresponding terminal shaped protrusions 6a of the mold 6. Then if required, the NAND type flash memory device 2

is floated and positioned through supporting pieces (not shown) for the bottom walls 6c of the mold 6. A concrete example thereof includes that both of a frame section for loading the NAND type flash memory device 2 and the external connection terminals 5 are supported on the mold 6 by using the other thin frame bars. In this way, after positioning and arranging the NAND type flash memory device 2 within the mold 6, the control proceeds to inject sealing resin 3 such as epoxy resin, coating and sealing the NAND type flash memory device 2 together with the recessed shaped external connection terminals 5 in unitary shape by insulative resin 3, and forming into a plate shape. Thereafter, the walls or mold pieces 6b, 6c, and 6d of the assembled and formed mold 6 are separated each other from the plate shaped mold to produce the external storage device as shown in Figs. 1 and 2.

[0017] In Figs. 1 and 2, numeral 1a depicts direction of the external storage device 1, showing the mechanical attaching and connection for the storage equipment / device main and a mark for preventing or avoiding erroneous attaching. The mark 1a showing directionality is not limited to a corner section or one corner, but it may preferably be set to simultaneously use a guide function in detachable structure of the equipment / devices main. A connection for the external connection terminals 5 of the external storage device 1 may preferably be non-contact connection systems such as radio waves or lights in addition to mechanical connections.

Embodiment 2

[0018] Figs. 5 to 7 are perspective views showing outline of structures together with operation modes of an external storage device unit according to the invention. In this example, the external storage device 1 formed as described in the embodiment 1 is in condition of one-side constituent element. The storage medium series element containing at least the non-volatile semiconductor memory chip 2 is coated and sealed by the insulator 3 such as epoxy resin, to be connected with the input / output terminals of both the card shape molded external storage device main and the storage medium series element coated and incorporated by the insulator 3, and to produce the external storage device 1 having the external connection terminals 5 led and exposed in manner of a concaved surface on a periphery and surface of the external storage device main, where such external storage device 1 is premised in this embodiment. As shown in Fig. 5, when inserting or extracting the external storage device 1 in or from the engage type unit 7 of the storage equipment / device main by one touch operation, then depending on such insertion or extraction, the external connection terminal 5 led and exposed on opposing edges is resiliently connected to or disconnected from an electric contact 8 arranged on an engaging section of the engaging unit 7.

[0019] Fig. 6 shows in detail a structural example of

the engaging unit 7, where opposing surfaces of a pair of supporters 7a and 7a', which are arranged oppositely each other, are engaged with end surfaces led from the external connection terminals 5 of the external storage device 1 to produce a slidable form. The electric contacts 8 corresponding to the external connection terminals 5 of the external storage device 1 are electrically insulatively arranged on a slidably formed region on the opposing surfaces of the supporters 7a and 7a'. It is of course that these electric contacts 8 are electrically connected to the main body-side of the storage equipment / device and form the necessary electric circuit.

[0020] Numeral 7b depicts a slide stop member of the external storage device 1 for sliding the opposing surfaces of the pair of supporters 7a and 7a'. When the external storage device 1 is inserted and tip end thereof is made in contact with the slide stop member 7b, pin type springs 7c and 7c' are rotated in a reverse direction by pressure due to such contact. By the rotation of the pin type springs 7c and 7c', the electric contacts 8 arranged on the opposing surfaces of the supporters 7a and 7a' are made contact in corresponding to the external connection terminals 5 of thus inserted external storage device 1 to achieve necessary electrical connection. Here, an automatic fixing and setting are completed by inserting the external storage device 1 into the engaging unit 7 to attach it on the predetermined position. Depressing the push button (not shown) arranged on a main body of the unit, which provides release of a fixed engaging piece (not shown) and extraction of the external storage device 1. On releasing the fixed engaging piece, the external storage device 1 is automatically extracted by the reverse rotation of the pin type springs 7c and 7c' and the contacts of the external connection terminals 5 and the electric contacts 8 are released.

[0021] According to the invention, the engaging unit 7 is formed as developmentally shown in Fig. 7, where the pair of supporters 7a and 7a' may preferably be arranged movable in the opposing direction through the resilient type spring 7d by a pair of cylinders 7e and 7e' respectively. Even in this structure, the electric contacts 8, which correspond to the external connection terminals 5 led and exposed on opposing end surfaces of the external storage device 1, are electrically insulated with each other and arranged on the opposing surfaces of the supporters 7a and 7a'. Of course, these electric contacts 8 are electrically connected to the storage equipment / device main body side and forms the necessary electric circuit. Numeral 7b' depicts an insertion stop member when the external storage device 1 is inserted. In case where the external storage device 1 is inserted to allow the contact of the external storage device 1 to be in contact with the insertion stop member 7b', pressure of such contact rotates the resilient type springs 7c and 7c' reverse to an energizing direction, such rotation forwards oppositely the supporters 7a and 7a' to press and contact the electric contacts 8 in corresponding to the external connection terminals 5 of thus inserted ex-

ternal storage device 1 to achieve the required electric connection. On the other hand, by extracting the external storage device 1, the pin type springs 7c and 7c' are reversally rotated, and it is correspondingly pushed out.

As is the case shown in Fig. 6, the external storage device 1 is inserted into the engaging unit 7 and attached on the predetermined position, then an automatic fixed setting is performed. On releasing the fixed setting, it is automatically pushed out by the reverse rotation of the pin type springs 7c and 7c', and the contacts of both the external connection terminals 5 and the electric contacts 8 are released.

Embodiment 3

[0022] Figs. 8 and 9 are perspective views showing other different examples in external storage device units according to the invention respectively. In the drawings, the external storage device 1 constructed as follows is in a one-side constituent element. The storage medium series element containing at least the non-volatile semiconductor memory chip 2 is coated and sealed by the insulator 3, to be connected with input / output terminals of both the external storage device main formed in a card shape and the storage medium series element incorporated with coating of the insulator 3, and to produce the external storage device 1 having the external connection terminals 5 led and exposed in a manner of a concaved or plane shape on the peripheral end surface or the main surface of the external storage device main, where such external storage device 1 is premised on this embodiment. The external storage device 1, as shown in Figs. 8 and 9, can optionally be attached or detached on an external storage device unit main 9 provided with a region or window 9a capable of attaching and detaching the external storage device 1. In other words, the external storage device 1 is constructed in that the external storage device unit main 9 including a control device for the external storage device 1 to be engaged and attached is combined with a connection section formed of the electric contacts 8 resiliently connecting or disconnecting on the external connection terminals 5 depending on attaching or detaching of the external storage device 1 to the region 9a (that is a window and forms an engaging / attaching section) detachable for the external storage device 1. This functions that, as in the other embodiments described, the external storage device 1 is engaged, attached and detached by one touch operation to the engaging / attaching section or region 9a of the external storage device unit main 9 to produce the required functions such as recording etc.

[0023] In the structure in Fig. 8, the electric contacts 8 corresponding to the external connection terminals 5 of the external storage device 1 are resiliently provided on the engaging / attaching section 9a of the external storage device unit main 9. On engaging, attaching and setting the external storage device 1, a pressure force thereof allows the electric contacts 8 to resiliently con-

tact with the external connection terminals 5 led and exposed in a plane manner on the main surface (backside surface) of the external storage device 1, and such readed pressure resets the external storage device 1, simultaneously the electric contacts 8 is resiliently detached from the external connection terminals 5.

[0024] In Fig. 9, when the external storage device 1 is engaged, attached, and set on the engaging / attaching section 9a of the external storage device unit main 9, the external connection terminals 5, which are placed on the end surface in the attaching or inserting direction, resiliently contacts with the electric contacts 8 arranged on a contact surface of the engaging / attaching section 9a. On resetting to engage or attach the external storage device 1, engaging or hooking is released and allows the electric contacts 8 to detach from the external connection terminals 5, where, if the external storage device unit main is formed into a card shape, then preferably, the external storage device unit is easy to carry as a set. The conventional card type external storage device so called IC memory card, functions as one IC memory card such that, pin connections are loaded in accordance with JEIDA (Japanese Electric Industry Development Association) or PCMCIA, or the other semiconductor devices such as interface circuits or semiconductor memory control circuits or switching circuits are loaded on the substrate. To the contrary, the present invention features that only the semiconductor memory is optionally separated and used, this therefore provides a great advantage.

[0025] It is understood that the invention is not limited to the embodiments as described above and the foregoing and various changes are taken therein without departing from the subject matter of the invention.

[0026] As hereinbefore fully described, in the external storage device and the external storage device unit according to the invention, various advantages are provided as listed below. For the external storage device, a high integration is provided, where the non-volatile semiconductor memory device having a larger memory capacity even in one compact chip is used as a main memory, which is molded unitarily into a card shape by insulative resin etc. Such use of the unitary mold type and the non-volatile semiconductor memory device readily provides optional detaching, easier carrying, easier handling, and thin and compact structure, and thus resulting in lower cost performance. In the unitary form thereof, since the external connection terminals are made into a concaved surface or a flat surface without protruding from the coated or sealed resin layer surface, an upgraded slidability is obtained, this eliminates damage and erroneous connection of the external connection terminals.

[0027] The external storage device unit also exhibits the graded releasability and improved reliability in function. In particular, various advantages in practical use of the external storage device unit include optional detaching of the external storage device, easier carrying with-

out possibility of damaging from the outside, and a larger recording / saving capacity of the data even in a compact size.

Claims

1. A plate-shaped external storage device (1) for storing data which is exchangeably connected with a host device, comprising:
 - a non-volatile semiconductor memory device (2), having input/output terminals;
 - external connection terminals (5) connected to the input/output terminals, the external connection terminals (5) having end surfaces; and
 - an insulator (3) coating and sealing the memory device (2) and the external connection terminals (5) unitarily into a molded plate to form the plate-shaped external storage device;
 - wherein the end surface of the external connection terminals being exposed on at least two peripheral surfaces (5b) opposed each other of the plate-shaped external storage device (1), characterised in that the end surfaces of the external connection terminals (5) are exposed in concavities (5a) on the peripheral surfaces (5b) of the plate-shaped external storage device (1).
2. A plate-shaped external storage device (1) as claimed in claim 1, wherein the non-volatile semiconductor memory device (2) is a NAND flash type non-volatile semiconductor memory device.
3. A plate-shaped external storage device (1) as claimed in claim 1, wherein the insulator (3) is epoxy resin.
4. A plate-shaped external storage device as claimed in claim 1, further comprising a control semiconductor for controlling the non-volatile semiconductor memory device, and the control semiconductor is incorporated in the plate-shaped external storage device.
5. A plate-shaped external storage device as claimed in claim 2, further comprising a control semiconductor for controlling the NAND flash type non-volatile semiconductor memory device, and the control semiconductor is incorporated in the plate-shaped external storage device.
6. A plate-shaped external storage device as claimed in claim 2, wherein the plate-shaped external storage device having an indicating mark showing a direction.
7. A plate-shaped external storage device as claimed

in claim 6, wherein the indicating mark is formed at least one corner of the plate-shaped external storage device.

8. An external storage device unit comprising a plate-shaped external storage device according to any preceding claim, further comprising: an engaging section (7) having at least a pair of mating surfaces (7a, 7a') for the plate-shaped external storage device (1), and electric contacts (8) arranged on the mated surface of the engaging section (7), the electric contacts capable of resiliently connecting to or disconnecting from the external connection terminals (5) corresponding to engaging, attaching or detaching of the external storage device (1) to the engaging section (7).
9. An external storage device unit (17) as claimed in claim 8, wherein the electric contacts (8) are resilient type electrical contacts (8) having a convex shape so that the plate-shaped external storage device (1) is electrically connected when engaged.
10. An external storage device unit as claimed in claim 8, further comprising a circuit having a memory control circuit, an interface circuit and a switching circuit of the external storage device.
11. An external storage device unit (17) according to any of claims 8-10, wherein the external storage device unit (1) is formed in a card shape.

Patentansprüche

1. Plattenförmige, externe Speicheranordnung (1) zum Speichern von Daten, die austauschbar mit einer Host-Anordnung verbunden ist, enthaltend:
eine nicht-flüchtige Halbleiter-Speicheranordnung (2) mit Eingangs- und Ausgangsanschlüssen, externe Verbindungsanschlüsse, die mit den Eingangs- und Ausgangsanschlüssen verbunden sind, wobei die externen Verbindungsanschlüsse (5) Endflächen besitzen; und wobei ein Isolierstoff (3) die Speicheranordnung (2) und die externen Verbindungsanschlüsse (5) einheitlich beschichtet und in eine gegossene Platte Guß-versiegelt, um die plattenförmige, externe Speicheranordnung zu bilden;
wobei die Endfläche der externen Verbindungsanschlüsse auf wenigstens zwei periphere, gegeneinander gerichtete Flächen (6b) der plattenförmigen, externen Speicheranordnung (1) ausgerichtet sind, dadurch gekennzeichnet, daß die Endflächen der externen Ver-

bindungsanschlüsse (5) in Konkavitäten (6a) auf den peripheren Flächen (6b) der plattenförmigen, externen Speicheranordnung (1) ausgerichtet sind.

2. Plattenförmige, externe Speicheranordnung (1), wie in Anspruch 1 beansprucht, wobei die nicht-flüchtige Halbleiter-Speicheranordnung (2) eine nicht-flüchtige Halbleiter-Speicheranordnung vom NAND-Flash-Typ ist.
3. Plattenförmige, externe Speicheranordnung (1), wie in Anspruch 1 beansprucht, wobei der Isolierstoff (3) Epoxyharz ist.
4. Plattenförmige, externe Speicheranordnung, wie in Anspruch 1 beansprucht, weiter enthaltend einen Steuerhalbleiter zum Ansteuern der nicht-flüchtigen Halbleiter-Speicheranordnung, wobei der Steuerhalbleiter in der plattenförmigen, externen Speicheranordnung eingebaut ist.
5. Plattenförmige, externe Speicheranordnung, wie in Anspruch 2 beansprucht, weiter enthaltend einen Steuerhalbleiter zum Ansteuern der nicht-flüchtigen Halbleiter-Speicheranordnung vom NAND-Flash-Typ, wobei der Steuerhalbleiter in der plattenförmigen, externen Speicheranordnung eingebaut ist.
6. Plattenförmige, externe Speicheranordnung, wie in Anspruch 2 beansprucht, wobei die plattenförmige, externe Speicheranordnung eine Indizierungsmarke besitzt, die eine Richtung anzeigt.
7. Plattenförmige, externe Speicheranordnung, wie in Anspruch 6 beansprucht, wobei die Indizierungsmarke wenigstens an einer Ecke der plattenförmigen, externen Speicheranordnung gebildet ist.
8. Externe Speicheranordnungseinheit, enthaltend eine plattenförmige, externe Speicheranordnung gemäß irgendeinem der vorhergehenden Ansprüche, weiter enthaltend: einen Eingriffsabschnitt (7) mit wenigstens einem Paar zueinander passender Oberflächen (7a, 7a') für die plattenförmige, externe Speicheranordnung (1), und elektrische Kontakte (8), die auf der angepaßten Oberfläche des Eingriffsabschnitts (7) angeordnet sind, wobei die elektrischen Kontakte dazu imstande sind, eine Verbindung zu den externen Verbindungsanschlüssen (5) herzustellen oder diese zu trennen, je nachdem ob die externe Speicheranordnung (1) mit dem Eingriffsabschnitt (7) im Eingriff steht, daran befestigt ist oder davon gelöst ist.
9. Externe Speicheranordnungseinheit (1, 7), wie in Anspruch 8 beansprucht, wobei die elektrischen

- Kontakte (8) elektrische Kontakte (8) vom flexiblen Typ sind, die eine konvexe Gestalt besitzen, so daß die plattenförmige, externe Speicheranordnung (1) elektrisch verbunden ist, wenn sie im Eingriff stehen
10. Externe Speicheranordnungseinheit, wie in Anspruch 8 beansprucht, weiter enthaltend eine Schaltung mit einer Speichersteuerschaltung, einer Schnittstellenschaltung und einer Schalteinrichtung der externen Speicheranordnung.
11. Externe Speicheranordnungseinheit (1, 7) gemäß irgendeinem der Ansprüche 8-10, wobei die externe Speicheranordnungseinheit (1) in einer Kartengestalt gebildet ist.

Revendications

1. Dispositif de stockage externe en forme de plaque (1) pour stocker des données qui est connecté avec un dispositif hôte de manière à pouvoir réaliser un échange, comprenant:
 - un dispositif de mémoire à semiconducteur non volatile (2) comportant des bornes d'entrée/sortie;
 - des bornes de connexion externes (5) connectées aux bornes d'entrée/sortie, les bornes de connexion externes (5) comportant des surfaces d'extrémité; et
 - un isolant (3) qui recouvre et assure le scellement du dispositif de mémoire (2) et des bornes de connexion externes (5) de façon unitaire selon une plaque moulée afin de former le dispositif de stockage externe en forme de plaque; dans lequel la surface d'extrémité des bornes de connexion externes est exposée sur au moins deux surfaces périphériques (6b) opposées l'une à l'autre du dispositif de stockage externe en forme de plaque (1), caractérisé en ce que les surfaces d'extrémité des bornes de connexion externes (5) sont exposées dans des concavités (6a) sur les surfaces périphériques (6b) du dispositif de stockage externe en forme de plaque (1).
2. Dispositif de stockage externe en forme de plaque (1) selon la revendication 1, dans lequel le dispositif de mémoire à semiconducteur non volatile (2) est un dispositif de mémoire à semiconducteur non volatile du type flash NON-ET.
3. Dispositif de stockage externe en forme de plaque (1) selon la revendication 1, dans lequel l'isolant (3) est une résine époxy.
4. Dispositif de stockage externe en forme de plaque selon la revendication 1, comprenant en outre un semiconducteur de commande pour commander le dispositif de mémoire à semiconducteur non volatile, et le semiconducteur de commande est incorporé dans le dispositif de stockage externe en forme de plaque.
5. Dispositif de stockage externe en forme de plaque selon la revendication 2, comprenant en outre un semiconducteur de commande pour commander le dispositif de mémoire à semiconducteur non volatile du type flash NON-ET, et le semiconducteur de commande est incorporé dans le dispositif de stockage externe en forme de plaque.
6. Dispositif de stockage externe en forme de plaque selon la revendication 2, dans lequel le dispositif de stockage externe en forme de plaque comprend un repère d'indication qui indique une direction.
7. Dispositif de stockage externe en forme de plaque selon la revendication 6, dans lequel le repère d'indication est formé au moins au niveau d'un angle du dispositif de stockage externe en forme de plaque.
8. Unité de dispositif de stockage externe comprenant un dispositif de stockage externe en forme de plaque selon l'une quelconque des revendications précédentes, comprenant en outre: une section de coopération (7) comportant au moins une paire de surfaces de conjugaison (7a, 7a') pour le dispositif de stockage externe en forme de plaque (1), et des contacts électriques (8) agencés sur la surface conjuguée de la section de coopération (7), les contacts électriques pouvant se connecter de façon élastique aux bornes de connexion externes (5) ou s'en déconnecter de façon élastique en correspondance avec la mise en coopération, la fixation ou la libération du dispositif de stockage externe (1) vis-à-vis de la section de coopération (7).
9. Unité de dispositif de stockage externe (1, 7) selon la revendication 8, dans lequel les contacts électriques (8) sont des contacts électriques du type élastique (8) présentant une forme rendue convexe de telle sorte que le dispositif de stockage externe en forme de plaque (1) soit connecté électriquement lorsqu'il est mis en coopération.
10. Unité de dispositif de stockage externe selon la revendication 8, comprenant en outre un circuit comportant un circuit de commande de mémoire, un circuit d'interface et un circuit de commutation du dispositif de stockage externe.
11. Unité de dispositif de stockage externe (1, 7) selon

l'une quelconque des revendications 8 à 10, dans lequel l'unité de dispositif de stockage externe (1) présente la forme d'une carte,

5

10

15

20

25

30

35

40

45

50

55

8

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

